



UT.Minipol.1 Polisher Single Position Fiber Polisher

UT.MINIPOL.1 is a fiber polishing system designed for prototyping and small production.

All connector types may be prepared by the system, including SC, FC, ST, D4, SMA, Bare fiber, PC, and flat polishes are all accommodated by simple changes of the lap and/or the workholder.

A factory-set reciprocating arm movement rides the rotating lap producing high performance. This produces quality results at a low price.

UT.MINIPOL.1 allows for use as a retro-polishing machine or as a quick factory-use system whether used singly, or in tandem with other units.

The system can be powered by 110 or 220 VAC converter or by a standard 12 V battery. A wide variety of workholders are available for extending the use of the system at any time.



Product Highlights

- Retro-polishing – bring already-installed connectors up to current industry requirements
- Wide range of holders
- Low cost machinery solution

Machine Specifications

Lap diameter	4 inch OD
Weight	2.2 kg (5 lbs.)
Power supply	12 V converter
Timer	10 – 120 seconds

1 Position Connector Holders

Order Code	Item
2803.5	SMA (905)
2803.6	SMA (906)
2804.1	ST
2805.1	SC
2805.8	SC-APC
2811.1	Ferrule Only (2.5 mm)
2811.2	Ferrule Only (1.25 mm)
2811.8	Angled Ferrule Only (2.5 mm)
2811.9	Angled Ferrule Only (1.25 mm)
2811.XX	Contact Holder Assembly (specify contact O.D. & type)
2813.1	MU
2813.8	MU-APC
2814.1	FC
2814.8	FC-APC
2815.1	LC
2815.8	LC-APC