

PbS Detectors Cooled Standard PB27-Series

Description

The PB27 series is a collection of TE cooled photoconductive single element PbS detectors that operate at -20 °C to -35 °C with a 20% cut-off of 3.3 μm . This series is widely used in analytic, safety and radiometric applications especially when large active areas are requested.

Features

- Spectral range from 1 to 3.3 μm
- State of the art performance
- 100% test data

Applications

- Pulp and paper industry
- Non-contact temperature measurement
- Spark detection
- Flame control
- Moisture monitoring
- FTNIR

Versions

- TO-can (TO-37, TO-8, TO-8 with flange)
- Sapphire window as standard
- Custom versions available



Basic Characteristics

Part Number	Element Size [mm]	Aperture Size [mm]	Features	20% Cut-off Wavelength [μm] ^b	Peak Wavelength [μm] ^b	Peak Responsivity [V/W] ^{ac}		Time Constant [μs] ^b	
				Typ.	Typ.	Min.	Typ.	Typ.	Max.
PB27S1010T17M	1.0 x 1.0	dia. 6.35	1 stage cooling (max 1.6 W), TO-37, medium cap	3.3	2.6	1300000	1950000	800	1600
PB27S2020T17M	2.0 x 2.0	dia. 6.35	1 stage cooling (max 1.6 W), TO-37, medium cap	3.3	2.6	650000	975000	800	1600
PB27S3030T17M	3.0 x 3.0	dia. 6.35	1 stage cooling (1 max 1.6 W), TO-37, medium cap	3.3	2.6	430000	650000	800	1600
PB27S5050T1S6M	5.0 x 5.0	dia. 9.5	1 stage cooling superior, TO-8 flange, medium cap	3.3	2.6	260000	390000	800	1600
PB27S6060T1S6M	6.0 x 6.0	dia. 9.5	1 stage cooling superior, TO-8 flange, medium cap	3.3	2.6	215000	325000	800	1600
PB27S2020T26L	2.0 x 2.0	dia. 9.5	2 stage cooling (max 1.4 W), TO-8 flange, large cap	3.3	2.6	660000	1000000	1250	2500
PB27S3030T26L	3.0 x 3.0	dia. 9.5		3.3	2.6	440000	660000	1250	2500

Further Versions in progress

Notes:

^a Measured with 500 K blackbody. Bias is 50 V/mm with 1 MOhm load in series. Chopping frequency is 650 Hz.

^b Parameter not 100% tested.

^c Without filter/window

Cooling Characteristics

Part Number	Element Size [mm]	Typ. Detector Operating Temperature [°C] ^b	Max. Cooler Power	Delta T @ max. Cool [°C]		Optional Package Versions
			Typ.	Min.	Typ.	
PB27S1010T17M	1.0 x 1.0	-20	1.2 V @ 1.4 A	40	45	TO-8
PB27S2020T17M	2.0 x 2.0	-20	1.2 V @ 1.4 A	40	45	TO-8
PB27S3030T17M	3.0 x 3.0	-20	1.2 V @ 1.4 A	40	45	TO-8
PB27S5050T1S6M	5.0 x 5.0	-25	2.2 V @ 1.4 A	45	50	TO-8
PB27S6060T1S6M	6.0 x 6.0	-25	2.2 V @ 1.4 A	45	50	TO-8
PB27S2020T26L	2.0 x 2.0	-35	1.2 V @ 1.2 A	55	60	TO-8
PB27S3030T26L	3.0 x 3.0	-35	1.2 V @ 1.2 A	55	60	TO-8

^b Valid with sufficient heat sinking only!

Electro-Optical Characteristics

Part Number	Element Size [mm]	Noise Density (rms) [$\mu\text{V}/\text{Hz}^{1/2}$] ^a		Peak D* [$\text{cm Hz}^{1/2}/\text{W}$] ^{abc}		Peak D* [$\text{cm Hz}^{1/2}/\text{W}$] ^{ac}		Dark Resistance [M Ω /square]		
		@ 90 Hz ^b	@ 650 Hz	@ 90 Hz	@ 90 Hz	@ 650 Hz	@ 650 Hz	Min.	Typ.	Max.
		Typ.	Typ.	Min.	Typ.	Min.	Typ.			
PB27S1010T17M	1.0 x 1.0	TBD	TBD	3.5 E+10	6.0 E+10	1.0 E+11	1.65 E+11	1.5	3.0	10
PB27S2020T17M	2.0 x 2.0	TBD	TBD	3.5 E+10	6.0 E+10	1.0 E+11	1.65 E+11	1.5	3.0	10
PB27S3030T17M	3.0 x 3.0	TBD	TBD	3.5 E+10	6.0 E+10	1.0 E+11	1.65 E+11	1.5	3.0	10
PB27S5050T1S6M	5.0 x 5.0	TBD	TBD	2.5 E+10	5.0 E+10	8.0 E+10	1.5 E+11	1.5	3.0	10
PB27S6060T1S6M	6.0 x 6.0	TBD	TBD	2.5 E+10	5.0 E+10	8.0 E+10	1.5 E+11	1.5	3.0	10
PB27S2020T26L	2.0 x 2.0	TBD	TBD	5.0 E+10	9.0 E+10	1.5 E+11	2.75 E+11	2.5	5.0	15
PB27S3030T26L	3.0 x 3.0	TBD	TBD	5.0 E+10	9.0 E+10	1.5 E+11	2.75 E+11	2.5	5.0	15

Notes:

^a Measured with 500 K blackbody. Bias is 50 V/mm with 1 M Ω load in series. Bandwidth of test setup is 1 Hz.

^b Parameter not 100% tested.

^c Without filter/window

All specifications apply at or near max. cooling temp. with heat sink at +25 °C.

Package Drawings

All standard packages, dimensions and tolerances are shown in our supplementary datasheet „PbS- / PbSe Detectors - Package Drawings & Cooling Specifications“.

Product Changes

LASER COMPONENTS reserves the right to make changes to the product(s) or information contained herein without notice. No liability is assumed as a result of their use or application.

Ordering Information

Products can be ordered directly from LASER COMPONENTS or its representatives. For a complete listing of representatives, visit our website at www.lasercomponents.com

Germany & Other Countries

Laser Components Germany GmbH
Tel: +49 8142 2864 - 0
Fax: +49 8142 2864 - 11
info@lasercomponents.com
www.lasercomponents.com

France

Laser Components S.A.S.
Tel: +33 1 39 59 52 25
Fax: +33 1 39 59 53 50
info@lasercomponents.fr
www.lasercomponents.fr

United Kingdom

Laser Components (UK) Ltd.
Tel: +44 1245 491 499
Fax: +44 1245 491 801
info@lasercomponents.co.uk
www.lasercomponents.co.uk

Nordic Countries

Laser Components Nordic AB
Tel: +46 31 703 71 73
Fax: +46 31 703 71 01
info@lasercomponents.se
www.lasercomponents.se

USA

Laser Components USA, Inc.
Tel: +1 603 821 - 7040
Fax: +1 603 821 - 7041
info@laser-components.com
www.laser-components.com