

*Bound to Innovate*

**OPTICAL FIBER STRIPPER**  
**ISO 9001 Certified**  
**S218R** Thermal Stripper  
**New & Improved!!**  
**Cordless, Light, & Quick**



**Key Features**

- Exceptional stripping for single and ribbon fiber.
- Simple Operation via built-in battery or AC power.
- Built-in battery recharger - battery always charging when AC power is connected.
- Durable Design
- Easy Maintenance on-Site

**Specifications**

Fiber Types	All fiber types, single to 12-fiber ribbons		
Clad Diameter	0.125mm		
Coating Diameter	0.25mm to 0.4mm for single fiber; 0.3mm to 0.4mm thickness for ribbons		
Power Source	DC 11 ~ 14V	AC 85 ~ 264V	* using S952 AC Adapter
Battery Running Time	Approximately 10 hrs.		
Charge Time	Approximately 2.5 hrs		* when unit is in off position
Operating Environment	Temperature: 0 ~ 40 °C Humidity: Below 95%		* non-condensing
Dimensions/Weight	125W x 48D x 41H [mm], 260g		* weight including battery

**Package & Accessories**

Model	Item	Part Number	Qty	Note
S218R	Main Body	S218R-01	1	
	Battery	S944	1	
	AC Adapter	S952	1	
	Hexagon Wrench	S218X-07	2	For replacing blade
	Screwdriver	S218X-20	1	For battery cover
	Manual	—	1	
S218R Optional Parts	Power Cord A	S218X-02	1	Cord used to connect S218R to splicer
	Single Fiber Adapter	S218X-03	1	Used when stripping single fiber without a fiber holder
	Spare Blade	S218X-06	1	



**FURUKAWA ELECTRIC CO., LTD.**

JE 188 2A5 TR 200