


HL40115MG


405 nm / 600 mW Violet Laser Diode

Outline



(Unit: mm)

Internal Circuit



Features

- Optical Output Power: 600 mW (CW)
- Violet Lasing: 400 ~ 410 nm
- Low Operating Current: 550 mA Typ.
- Low Operating Voltage: 4.2 V Typ.
- Built-in Monitor PD
- Package: $\phi 5.6$ mm
- Multiple transverse mode
- TE mode oscillation.

Application

- Direct Imaging for PCB
- Industry
- Bio & Medical
- Measurement

HL40115MG

Absolute Maximum Ratings (Tc=25°C)

Item	Symbol	Ratings	Unit
Optical Output Power	P _o	700	mW
LD Reverse Voltage	V _{R(LD)}	5	V
PD Reverse Voltage	V _{R(PD)}	20	V
Operating Temperature	T _{opr}	0 ~ +30	°C
Storage Temperature	T _{stg}	-40 ~ +85	°C

Optical and Electrical Characteristics (Tc=25°C)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Threshold Current	I _{th}	70	110	180	mA	-
Operating Current	I _{op}	450	500	650	mA	P _o =600 mW
Operating Voltage	V _{op}	3.8	4.2	4.6	V	P _o =600 mW
Beam Divergence Parallel to the Junction	θ _{//}	5	13	25	°	P _o =600 mW, Full angle 1/e ²
Beam Divergence Perpendicular to the Junction	θ _⊥	30	45	50	°	P _o =600 mW, Full angle 1/e ²
Lasing Wavelength	λ _p	400	405	410	nm	P _o =600 mW
Monitor Current (*1)	I _m	1	2	5	mA	P _o =600 mW, V _{R(PD)} =5V

*1 for only initial checking

HL40115MG

Cautions

1. Ushio, Inc. (Ushio) neither warrants nor grants licenses of any its lights or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document, Ushio bears no responsibility for problems that may arise with third party's right, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Please confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Ushio makes every attempt to ensure that its products are of high quality and reliability. However, contact our sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic safety equipment or medical equipment for life support.
4. Design your application so that the products are used within the ranges guaranteed by Ushio; particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Ushio bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Ushio product does not cause bodily injury, fire or other consequential damage due to operation of the Ushio product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Ushio.
7. Contact our sales office for any questions regarding this document or Ushio products.

1. The laser light is harmful to human body, especially to the eye, no matter whether exposed directly or indirectly. The laser beam shall only be observed or adjusted through infrared camera or equivalent.
2. This product (except violet laser diodes) contains gallium arsenide (GaAs), which may seriously endanger your health, even at very low doses. Please avoid actions which may create GaAs powder or gas, such as disassembly or performing chemical experiments, when you handle the product. When disposing of the product, please follow the local laws of your country and separate it from other waste, such as industrial waste and household garbage.

Important Notice

Performance figures, data, and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by Ushio before they become applicable to any particular order or contract. In accordance with the Ushio policy of continuous improvement, specifications may change without notice. Further details are available from any Ushio sales representative.



Caution - use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.

HL40115MG

Disclaimer

Product specifications and data shown in this datasheet are subject to change without notice for the purposes of improving product performance, reliability, design, or otherwise.

Product data and parameters in this datasheet are typical values based on reasonably up-to-date measurements.

Product data and parameters may vary by user application and over time.

Products shown in this datasheet are intended to be used for general electronic equipment. Products are not guaranteed for applications where product malfunction or failure may cause personal injury or death, including but not limited to life-supporting / saving devices; medical devices; safety devices; airplanes; aerospace equipment; automobiles; traffic control systems and nuclear reactor control systems.