

## MODULATOR

**MXER-LN series**

1550 nm band Very High Extinction Ratio Intensity Modulators

The MXER-LN series of intensity modulators is a family of high performance modulators exhibiting superior Extinction Ratio.

Their specific design relies on iXblue "Magic Junction" (patent n° US2008193077).

MXER-LN series intensity modulators are key devices in all applications where a combination of high extinction and high bandwidth is required: laser pulse picking prior optical amplification, pulse generation or lidar based sensing systems are a few examples, as well as fiber optics sensors.

**Features**

- Superior extinction ratio: 40 dB
- High bandwidth
- X-cut for high stability
- Low drive voltage
- Low insertion loss

**Applications**

- Pulse generation / picking
- Carrier suppression
- Fiber optics sensors
- Pulse applications

**Options**

- 20 GHz version
- 1060 nm, 1300 nm band versions

**Related Equipments**

- Pulsed driver DR-PL
- MBC Automatic Bias Controllers

**MXER-LN-10 Performance Highlights**


Parameter	Min	Typ	Max	Unit
Operating wavelength	1530	-	1625	nm
Insertion loss	-	3.5	-	dB
Extinction ratio	-	30, 35, 40	-	dB
Electro-optical bandwidth	10	-	-	GHz

Specifications given at 25 °C, 1550 nm

**MXER-LN-20 Performance Highlights**

Parameter	Min	Typ	Max	Unit
Operating wavelength	1530	-	1625	nm
Insertion loss	-	3.5	-	dB
Extinction ratio	-	30, 35, 40	-	dB
Electro-optical bandwidth	18	-	-	GHz

Specifications given at 25 °C, 1550 nm

**Extinction Ratio Response**

MODULATOR | **MXER-LN SERIES** | 2/5**MXER-LN-10**

10 GHz Very High Extinction Ratio Intensity Modulator

**Electrical Characteristics**

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Electro-optical bandwidth	S <sub>21</sub>	RF electrodes, from 2 GHz	10	12	-	GHz
Rise / fall times	tr / tr	Optical pulse, using DR-VE-10-MO	-	30	35	ps
Ripple S <sub>21</sub>	ΔS <sub>21</sub>	RF electrodes, f < 12 GHz	-	0.5	1	dB
Electrical return loss	S <sub>11</sub>	RF electrodes, 0 - 12 GHz	-	-12	-10	dB
Vπ RF @50 kHz	Vπ <sub>RF 50 kHz</sub>	RF electrodes, @ 1550 nm	-	5.5	6	V
Vπ RF @10 GHz	Vπ <sub>RF 10 GHz</sub>	RF electrodes, @ 1550 nm	-	6.5	7	V
Vπ DC electrodes	Vπ <sub>DC</sub>	DC electrodes	-	6.5	7	V
Impedance matching	Z <sub>in-RF</sub>	-	-	50	-	Ω
DC input impedance	Z <sub>in-DC</sub>	-	1	-	-	MΩ

**Optical Characteristics**

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Crystal	-	-			Lithium Niobate X-Cut Y-Prop	
Operating wavelength	λ	-	1530	1550	1625	nm
Insertion loss	IL	Without optical connectors*	-	3.5	5	dB
DC Extinction ratio	ER	Measured at 1550 nm by default, for other λ contact us	30 35 40	- - -	- - -	dB
Optical return loss	ORL	-	-40	-45	-40	dB
Chirp	α	-	-0.1	0	-0.1	-

All specifications given at 25 °C, 1550 nm, unless differently specified.

\* Consider an extra-loss up to 0.25 dB for each FC/APC optical connector

**Absolute Maximum Ratings**

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.

Parameter	Symbol	Min	Max	Unit
RF input power	EP <sub>in</sub>	-	28	dBm
Bias Voltage	V <sub>bias</sub>	-20	+20	V
Optical input power	OP <sub>in</sub>	-	20	dBm
Operating temperature	OT	0	+70	°C
Storage temperature	ST	-40	+85	°C



MODULATOR | **MXER-LN SERIES** | 3/5**MXER-LN-20**

20 GHz Very High Extinction Ratio Intensity Modulator

**Electrical Characteristics**

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Electro-optical bandwidth	$S_{21}$	RF electrodes, from 2 GHz	18	20	-	GHz
Rise / fall times	$t_r / t_f$	Optical pulse	-	20	25	ps
Ripple $S_{21}$	$\Delta S_{21}$	RF electrodes, $f < 18$ GHz	-	0.5	1	dB
Electrical return loss	$S_{11}$	RF electrodes, 0 - 18 GHz	-	-12	-10	dB
V <sub>π</sub> RF @50 kHz	$V_{\pi_{RF \text{ 50 kHz}}}$	RF electrodes, @ 1550 nm	-	5.5	6	V
V <sub>π</sub> DC electrodes	$V_{\pi_{DC}}$	DC electrodes	-	6.5	7	V
Impedance matching	$Z_{in-RF}$	-	-	50	-	$\Omega$
DC input impedance	$Z_{in-DC}$	-	1	-	-	$M\Omega$

**Optical Characteristics**

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Crystal	-	-				Lithium Niobate X-Cut Y-Prop
Operating wavelength	$\lambda$	-	1530	1550	1625	nm
Insertion loss	IL	Without optical connectors*	-	3.5	5	dB
DC Extinction ratio	ER	Measured at 1550 nm by default, for other $\lambda$ contact us	30 35 40	- - -	- - -	dB
Optical return loss	ORL	-	-40	-45	-40	dB
Chirp	$\alpha$	-	-0.1	0	-0.1	-

All specifications given at 25 °C, 1550 nm, unless differently specified.

\* Consider an extra-loss up to 0.25 dB for each FC/APC optical connector


**Absolute Maximum Ratings**

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.


Parameter	Symbol	Min	Max	Unit
RF input power	$EP_{in}$	-	28	dBm
Bias Voltage	$V_{bias}$	-20	+20	V
Optical input power	$OP_{in}$	-	20	dBm
Operating temperature	OT	0	+70	°C
Storage temperature	ST	-40	+85	°C

MODULATOR | MXER-LN SERIES | 4/5  
**MXER-LN-10 & 20**


**Typical S<sub>21</sub> Curve**




**Typical S<sub>11</sub> Curve**




**Extinction Ratio**




**Generated 80 ps Optical Pulse**



**Stability with Time and Temperature**



**Insertion Loss with Time and Temperature**




**exail**

## MODULATOR | MXER-LN SERIES | 5/5


### Mechanical Diagram and Pinout

All measurements in mm



Port	Function	Note
IN	Optical input port	Polarization maintaining fiber Corning PM 15-U25D Length: 1.5 meter, buffer diameter: 900 µm
OUT	Optical output port	Polarization maintaining fiber Corning PM 15-U25D Length: 1.5 meter, buffer diameter: 900 µm
RF	RF input port	Female K (SMA compatible)
1	Ground	Pin feed through diameter 1.0 mm
2	DC	Pin feed through diameter 1.0 mm
3, 4	Photodiode cathode, anode	Pin feed through diameter 1.0 mm

### Ordering information



### About us

Exail Photonics produces specialty optical fibers and Bragg gratings based fiber optics components and provides optical modulation solutions based on the company lithium niobate ( $\text{LiNbO}_3$ ) modulators and RF electronic modules. Exail Photonics serves a wide range of industries: sensing and instruments, defense, telecommunications, space and fiber lasers as well as research laboratories all over the world.

Exail reserves the right to change, at any time and without notice, the specifications, design, function or form of its products described herein. All statements, specification, technical information related to the products herein are given in good faith and based upon information believed to be reliable and accurate at the moment of printing. However, Exail provides no warranty (whether express or implied or statutory) to the description, sufficiency, accuracy or completeness, merchantability or fitness for a particular purpose of any information or specification detailed herein. No liability is assumed for any inaccuracies and/or as a result of use of the products. The user must validate all parameters for each application before any use and he shall assume all risks and responsibilities in connection with the use of the products.