



## Passive Cladding Pumped Fiber

VERSION: MD17/5  
RELEASE DATE: 04 JANUARY 2018

Datasheet

## All Silica Double Clad Fiber

Passive Double Clad Fiber (SMM900) is a passive, dual cladding, Multimode (MM) fiber that combines both Single-Mode (SM) and MM fiber characteristics within a single fiber. The fiber has a germano-silicate SM core, a pure silica inner cladding to guide the pump light and a fluorine doped secondary cladding to give outstanding power handling over a full range of environmental conditions. The fiber does not rely on a low index polymer coating, so it can be stripped, cleaved and spliced like a standard telecoms fiber, without the need to apply a low index recoat material.

SMM900 has been designed specifically to be used in conjunction with Fibercore's Dual Clad Erbium/Ytterbium Doped Fiber (CP1500Y), Multimode Pump Fiber (MM105) and Isolating Wavelength Division Multiplexer (CP-IWDM). In order to minimize losses throughout the system and maximize efficiency, the optical characteristics of these fibers have been matched for high splice compatibility.

### Advantages:

- All silica design
- No recoating required
- Stable in humid environments

### Typical applications:

- Telecoms
- Erbium Doped Fiber Amplifier (EDFA)
- Cable Television (CATV)
- Fiber laser
- Biomedical illumination

### Related Products:

- Dual Clad Erbium/Ytterbium Doped Fiber (CP1500Y)
- Large Core Fiber (MM105)
- Isolating Wavelength Division Multiplexer (CP-IWDM)

### Product Variant:

- **SMM900** Double clad passive fiber with SM core and MM pump guide

### Specifications

	SMM900
<b>Single-Mode Core</b>	
Mode Field Diameter (µm)	6.5 - 8.2 @1550nm
Numerical Aperture	0.18 - 0.20
Cut-Off Wavelength (nm)	870 - 970
Attenuation (dB/km)	4 (nominal) @1550nm
Core Concentricity (µm)	≤0.75
<b>Pump Guide</b>	
Diameter (µm)	100 - 104
Numerical Aperture	0.24 - 0.28
<b>General</b>	
Cladding Diameter (µm)	125 ± 1
Proof Test (%)	1 (100 kpsi)
Coating Diameter (µm)	245 ± 7
Coating Type	Dual Layer Acrylate
Operating Temperature (°C)	-55 to +85