







FURUKAWA ELECTRIC

collected in the waste bin.

Consistent cleaving quality

05/23 / V1 / MC-IF / fitel/s327-cleaver

1



Specification	
Description	\$327
Applicable fiber	Silica
Fiber count	Single fiber
	Ribbon fiber 250 µm: 2~12 fiber ribbon 200 µm: 2~16 fiber ribbon
Clad diameter	125 µm
Coating diameter	Single fiber: 0.20~3.0 mm
	Ribbon fiber: 0.20~0.40 mm×0.25 mm pitch 0.20~0.40 mm×0.20 mm pitch
Cleave length	Single fiber: 3mm~*1
	Tape: 10mm~
Cutting blade life	65,000 fiber (2,500 fiber per cutting blade position)*2
Dimension	88W×93D×54H mm (Close for carrying)
Weight	320 g

^{*1} Cutting lengths of more than 3 mmbut less than 5 mm are only available with a coating diameter of 0.25 mm or less.
*2 The cutting blade life depends on the operation environment and condition. The number can vary and is not guaranteed.
0.20 mm pitch ribbon fiber decrease of cleaves.

Standard package				
Item	P/N	Quantity		
S327 Main Body	S327A-01	1		
Waste Bin	S327X-12	1		
Hexagonal Wrench	S327X-16	2		
Carrying Case	S327X-17	1		
Single Fiber Adapter*3	S327X-18	1		
Operating Instructions	FTS-B616	1		

^{*3} Single Fiber Adaptor scales 5~16 mm

Optional components

Item	P/N	SPQ
Waste Bin	S327X-12	1
Carrying Case	S327X-17	3
Single Fiber Adapter*3	S327X-18	1
Blade Exchange Set*4	S327X-24	1





Carrying Case







Blade Exchange Set (Optional component)

FURUKAWA ELECTRIC CO., LTD.

Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in Japan. In addition, the Export Administration Regulations (EAR) of the United States may be applicable. In cases where exporting or resporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of Japan or the Department of Commerce of the United States for details about procedures.

JE-256 2303 TR 100 D

 ^{*3} Single Fiber Adaptor scales 5-16 mm
 *4 If parts other than Blade, such as the Rubber pad, are worn out, replacing Blade alone may not restore the initial performance.

^{*} Please understand that contents of this catalog may change without notice.