

# SPECIFICATIONS

Return Loss	Single Mode	FTTX	Multimode
Source Wavelength	1310nm, 1550nm	1310nm, 1550nm, 1490nm, 1625nm	850nm, 1300nm
Calibrated Measurement Range	-10dB to -80dB	-10dB to -80dB	-10dB to -58dB
Measurement Linearity	±1dB (-12dB to -72dB)	±1dB (-12dB to -72dB)	±1dB (-10dB to -45dB)
Distance Range		up to 2500 meters	
Mandrel-free minimum distance		1.7 meters (both reflections <-45dB)	

Insertion Loss	Single Mode	FTTX	Multimode
Source Center Wavelength	±30nm from nominal	±30nm from nominal	±30nm from nominal
Source Bandwidth	<10nm	<10nm	<140nm (850nm) <200nm (1300nm)
Internal Fiber	9/125µm (SMF28)	9/125µm (SMF28)	50/125µm, 62.5/125µm, 105/125µm
Launch Condition	N/A	N/A	Available upon request
Output Power* (typical)	-1.5dBm	-2.5dBm	-18dBm(850nm) -20dBm(1300nm): 62.5/125µm
Insertion Loss Stability**	±0.02dB	±0.02dB	±0.02dB

#### Measurement Linearity (Relative Accuracy)\*\*\*

Deviation ± 0.05dB	0dBm to -65dBm at 1490nm
Deviation ± 0.01dB	<10dB power variation

\*For single channel systems. \*\*Over 1 hour with a max. change of 1°C. \*\*\*For 1, 2, and 3mm detectors.

Optical Power Meter	1mm InGaAs	3mm InGaAs	5mm InGaAs	10mm InGaAs	3mm Silicon
Measurement Range	+6dBm to -72dBm at 1490nm	+3dBm to -72dBm at 1490nm	0dBm to -65dBm at 1490nm	0dBm to -55dBm at 1490nm	0dBm to -65dBm at 980nm
Wavelength Range		850nm to 1650nm			400nm to 1100nm
Selectable Wavelength		Standard wavelengths (850nm, 980nm, 1300nm, 1310nm, 1490nm, 1550nm, 1625nm)			Standard wavelengths (650nm, 850nm, 980nm)
Measurement Resolution (Display)			0.001dB		
Absolute Accuracy			±0.25 dB at calibration conditions for all NIST traceable wavelengths		

#### Measurement Linearity (Relative Accuracy)

Deviation ± 0.05dB	+3dBm to -65dBm at 1490nm	0dBm to -65dBm at 1490nm	0dBm to -55dBm at 1490nm	0dBm to -45dBm at 1490nm	0dBm to -55dBm at 980nm
Deviation ± 0.01dB	<10dB power variation	<10dB power variation	<10dB power variation	<10dB power variation	<10dB power variation

Source	1310nm/1550nm LASER	1310nm/1490nm/1550nm/1625nm LASER	850nm/1300nm LED
Source Center Wavelength	±30nm from nominal	±30nm from nominal	±30nm from nominal
Source Bandwidth	<10nm	<10nm	<140nm (850nm) <200nm (1300nm)
Internal Fiber	9/125µm (SMF28)	9/125µm (SMF28)	50/125µm, 62.5/125µm, 105/125µm
Launch Condition	N/A	N/A	Available upon request
Output Power (typical)	-1.5dBm	-2.5dBm	-18dBm(850nm) -20dBm(1300nm): 62.5/125µm
Source Stability*	±0.02dB	±0.02dB	±0.02dB

\* Over 1 hour with a max. change of 1°C.

Measurement Timing	Single Mode	FTTX	Multimode
IL and RL, Dual Wavelength	3s*	6s	3s*
Switching Time (Multichannel)		100ms	

\* Using the front panel in Dual IL/RL mode or running OPL-Pro with real-time update enabled.

Mainframe	Half-Rack Units	Full-Rack Units	OP710s/OP740s	OP940-SWs
Dimensions	8 ¾" x 3.5" x 12"	16 ¾" x 3.5" x 12"	16 ¾" x 3.5" x 8"	16 ¾" x 3.5" x 14"
Power Supply	90VAC ... 264VAC; 47Hz to 63Hz; 0.7Amps (115VAC) 0.4Amps (230VAC); Fuse: T1A, 250V			
Warm-up time		5-15 minutes		
Operating Temperature		5°C to 40°C		
Maximum Relative humidity*		80%		

\* For temperatures up to 31°C, decreasing linearly to 50% relative humidity at 40°C.

#### Laser Classifications

All OP940 Insertion Loss and Return Loss Test Sets utilize a **Class I Laser Source**. Unless otherwise noted, all OP250, OP715, and OP750 source units with internal laser sources utilize a **Class I Laser Source**. Unless otherwise noted, all OP815 and OP850 Insertion Loss Test Sets with internal laser sources utilize a **Class I Laser source**. All OP280 Visual Fault Finder units utilize a **Class III Laser Source**.

OptoTest strongly suggests that all necessary precautions be taken whenever any Class I or Class III laser source is used.

Specifications are subject to change, please confirm specific performance characteristics of the product at the time of ordering. All specifications are valid within temperature range of 18°C to 24°C unless otherwise noted. For additional specifications please contact OptoTest.

Doc: PS-GENSPECs Rev.D 11/7/18