

Data Sheet

# VIAVI T-BERD/MTS-8000 Scalable Multitest Platform

One solution that expands to more than 40 tests

### Keep ahead of the telecommunications technology curve

The VIAVI Solutions T-BERD®/MTS-8000 V2 is the industry's most innovative and versatile test solution for modern and next-generation network deployments.

Built to support current and ultra-high-speed transmission network testing needs, the T-BERD/MTS-8000 V2 embeds the latest state-of-the-art technology for those planning long-term investments and offers simply the best-in-test solution.



#### **Key Benefits**

- Multitest platform to accelerate deployment and maintenance of ultrahigh-speed networks
- Increased scalability with more than 40 applications and hundreds of test configurations
- Stay connected wherever you are with 3G, WiFi, Bluetooth, or Ethernet
- Increased efficiency cuts test time by 70 percent
- Seamless workflow with automated test sequences and on-the-go post-processing

#### **Kev Features**

- Modular test platform
- High-speed PowerPC processor with 100 GB SATA hard disk
- High-visibility touch-screen display
- Automated fiber connector inspection with IEC pass/fail analysis
- Built-in optical options including power meter, VFL, and talk set
- Compatible with T-BERD/MTS-6000 test modules

#### Applications

- Perform physical layer fiber characterization for high-speed CWDM/DWDM transmission networks
- Activate and commission next-generation transport and datacom services



# A full set of applications and utilities optimizes field-testing efficiency

The T-BERD/MTS-8000 V2 empowers technicians with an installation and maintenance platform that uniquely combines physical, optical, and transport/Ethernet testing capabilities.



## Stay connected wherever you are

The T-BERD/MTS-8000 V2 integrates various communication capabilities for remote access from anywhere, enabling data and setup uploads/downloads, remote coaching, and report delivery.



T-BERD/MTS-8000 Scalable Multitest Platform

2





- 10.4 inch touch screen
- 2 Battery indicator
- 3 On indicator
- 4 On/Off
- Export

- **6** Home page
- 7 File menu
- 8 Setup menu
- Results page
- Loud speaker
- 1 Start/Stop
- Script
- **B** Testing indicator
- Direction and validation keys
- Menu keys
- **6** WiFi option
- Bluetooth option
- 18 Removable hard disk
- (DC input
- Optical talk set option
- Optical power meter option
- VFL option
- **ॐ**1GE port
- Three USB 2.0 ports
- Mini USB 2.0 ports
- **ॐ** Headset jack

# Scalable multitest platform meets network requirements

With its stackable design, the T-BERD/MTS 8000 V2 provides the most scalable advanced solution for all of your optical testing needs. It is completely field-upgradeable to address both current and future testing requirements.













T-BERD/MTS-8000 Scalable Multitest Platform

06/20 / V03 / MC-IF / viavi/mts6000-8000/mts-8000



#### Specifications

Platform					
Display	10.4-inches TFT color touch screen				
	Resolution: 800 x 600				
Interfaces	3 x USB 2.0 ports				
	1 x mini-USB 2.0 port				
	RJ45 LAN 10/100/1000 Mbps				
	Built-in Bluetooth (optional)				
	Built-in WiFi 802.11 b/g/n (optional)				
Internal memory	2 GB (128 MB for storage)				
Batteries	Two rechargeable Li-ion (total of 200 W.h)				
Power supplies					
Standard	AC/DC adapter, input 100–250 V, 50–60 Hz, output 24 VDC, 6.25 A max. Electrical safety: EN60950 compliant				
High power	AC/DC adapter, input 100–250 V, 50–60 Hz, output 21 VDC, 10.5 A max., Electrical safety: EN60950 compliant				
Size with battery pack (W x H x D)	326 x 267x 93 mm (12.8 x 10.5 x 3.6 in)				
Weight with 2 batteries	t with 2 batteries 4.280 kg (9.44 lbs)				
Temperature					
Operating	−20 to +50°C (−4 to 122°F)				
Storage	-20 to +60°C (-4 to 140°F)				
Relative humidity	0 to 95% non condensing				
Built-in power meter	(optional)				
Calibrated wavelength	850, 1310, 1490, 1550, 1625, 1650 nm				
Wavelength range	800 to 1650 nm in 1 nm steps				
Accuracy <sup>2</sup>	± 0.2 dB				
Measurement range <sup>3</sup>	+5 to -50 dBm				
Maximum resolution	0.01 dB/0.01 nW				
Connector type	Universal push/pull (UPP)				
Visual fault locator (VI	L) (optional)				
Wavelength	650 nm				
Emission mode	CW, 1 Hz				
Laser class	Class 2 as per standards EN60825-1 and FDA21 CFR Part 1040.10				
Optical talk set (option	nal)				
Dynamic range	45 dB (typical)				

- 1. At 25°C after 20 minutes stabilization time and after zero setting
- 2. At calibrated wavelength (except 1650 nm)
  3. -45 dBm from 800 to 1250 nm

#### **Ordering Information**

Description	Part Number			
T-BERD/MTS-8000 V2 Scalable Multitest platform for standard use Includes 100 GB hard disk, 2 standard batteries and 150 W standard power supply	ETB8000E/EM8000E			
T-BERD/MTS-8000 V2 Scalable Multitest platform for high-power use Includes 100 GB hard disk, 2 high-power batteries, power supply (150, 220 or 300 W to be specified)	ETB8000EHP/EM8000EHP			
T-BERD/MTS-8000 V2 Scalable Multitest platform for a-la-carte configuration	ETB8000EBL/EM8000EBL			
2 plug-in receptacles for optical modules	E8100			
Dual-module carrier for MSAM, MSAM v2, OSA-110 modules	C8200			
Built-in optical power meter and VFL with 2.5 mm UPP connectors	E80EPMVFL			
Built-in optical talk set (adapter to be configured)	E80ETS			
Built-in talk set (adapter to be configured) and optical power meter (2.5 mm UPP connector)	E80ETSPM			
Built-in talk set (adapter to be configured), optical power meter and VFL (2.5 mm UPP connectors)	E80ETSPMVFL			
WiFi and Bluetooth options	E80EWIFIBLUE			
WiFi option	E80EWIFI			
Bluetooth option	E80EBLUE			
Standard Li ion battery	E80ELIION			
High-power Li ion battery	E80ELIIONHP			
100 GB SATA hard disk	E80EHDISK			
USB 2.0 Digital Video Scope Kit (P5000i), including 7 tips and soft case	EDFSCOPE5Ki			
Additional kickstand for multi-module configurations	E80KSTAND			
Cigarette lighter power adapter	E80LIGHTER			
Soft carrying case handling the platform and a combination of modules of 12 cm/4.75 in depth	E80SCASE2			
Soft carrying case handling the platform and a combination of modules of 7 cm/2.5 in	E80SCASE3			
Hard carrying case for T-BERD/MTS-8000 platform	E80HCASE1			

T-BERD/MTS-8000 Scalable Multitest Platform





# **VIAVI Care Support Plans**

## Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

For more Information: go to viavisolutions.com/viavicareplan

**Features** 

\*5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration
BronzeCare	Technician Efficiency	Premium	✓	✓	✓		
SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	✓	√*	✓

© 2020 VIAVI Solutions, Inc. Product specifications and descriptions in this document are subject to change without notice. 8000v2-ds-fop-tm-ae 30173071 902 0120