





NSL-07-005



FEATURES

- Passive resistance output
- Hermetic sealed
- Visible light response
- Sintered construction

DESCRIPTION

The NSL-07-005 is a dual element type 5 CdS photoconductive cell in a flat lens TO-5 hermetic package.

APPLICATIONS

- Military
- Industrial
- Medical

> Absolute Maximum Ratings

Part No.	Power Dissipation ¹ [mW]	Peak Voltage [V]	Operating Temperature [C]	Storage Temperature [C]	Package
NSL-07-005	200	150	-60 to +75	-60 to +75	TO-5

⁽¹⁾ Derate linearly to 0mW at 75°C

> Electrical and Optical Characteristics

Typical Characteristics per elements (T=23°C unless specified)										
Parameter	Test Conditions	Symbol	Min	Typical	Max	Unit				
Light Resistance	1 ftc., 2854°K (2)	R∟	75	-	200	ΚΩ				
Dark Resistance	5 sec after removal of test light.	R₀	2	-	-	МΩ				
Spectral Peak		λ _P	-	550	-	nm				
	Percent difference between the									
Matching	photocell halves with the higher resistance used as the reference.	-	-	-	20	%				

⁽²⁾ Cells light adapted at 30 to 50 Ftc for 16 hrs minimum prior to electrical tests.


Rev: A March 7, 2023 © 2022 Advanced Photonix. All rights reserved

⁽³⁾ Print "NSL-07-005" and date code "YYWW".



NSL-07-005

> Package Dimensions



Dimensions in mm.

> Soldering Conditions: 260°C 1/16 inch away from case for 3 seconds max.

LEGAL DISCLAIMER

All products, product specifications, and data are subject to change without notice to improve reliability, function, design, or otherwise. Advanced Photonix, its affiliates, agents, employees and all persons acting on its or their behalf (collectively, "Advanced Photonix"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Advanced Photonix makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Advanced Photonix disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability Statements regarding the suitability of products for certain types of applications are based on Advanced Photonix's knowledge of typical requirements that are often placed on Advanced Photonix products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different application is suitable for use may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Advanced Photonix's terms and conditions of purchase, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, Advanced Photonix products not exp

MATERIALS SAFETY

This product is free of conflict minerals and meets REACH compliance. Please see website for reports.

Rev: A March 7, 2023 © 2022 Advanced Photonix. All rights reserved.