



SD112-45-11-221





FEATURES

- Low Noise
- Blue Enhanced
- Single Supply Operation
- Feedback Circuit

DESCRIPTION

The **SD 112-45-11-221** is a detector/amplifier hybrid that combines a silicon photodiode with an opamp with a feedback resistor and capacitor, available in a hermetic TO-5 metal can package.

APPLICATIONS

- Military
- Industrial
- Medical

> Absolute Maximum Ratings

Part No.	Wavelength Range [nm]	Supply Voltage [V]	Operating Temperature [C]	Storage Temperature [C]	Package
SD112-45-11-221	300 to 1100	5 to 15*	-25 to +100	-55 to +125	TO-5
*Single supply					


Sirigle supply

> Electrical and Optical Characteristics

Typical Characteristics per elements (T=23°C unless specified)										
Parameter	Test Conditions	Symbol	Min	Typical	Max	Unit				
Cutoff Frequency	-	f _{3db}	-	0.13	-	KHz				
Transimpedance Gain	-	Gain	-	600		$\mathbf{M}\Omega$				
Sensitivity	λ= 633 nm	S	2.4x10 ⁸	2.8x10 ⁸		V/W				
Output Offset Voltage	-	Vos	-	0.08	1	mV				
Broadband Noise	f= 0.01Hz to 135 Hz	Vn	-	-	52	uV_{rms}				
Noise Equivalent Power	f= 0.01Hz to 135 Hz	NEP	-	3.5x10 ⁻¹⁴		W/√Hz				
Supply Current	-	ls	-	850	950	uA				
Output Voltage Swing	-	Vosw	0 to 4.7	-	0 to 14.7	V				

Rev: A August 17, 2021 © 2021 Advanced Photonix. All rights reserved.








SD112-45-11-221

> Schematic



LEGAL DISCLAIMER

All products, product specifications, and data are subject to change without notice to improve reliability, function, design, or otherwise. Advanced Photonix, its affiliates, agents, employees and all persons acting on its or their behalf (collectively, "Advanced Photonix"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Advanced Photonix makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Advanced Photonix disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability Statements regarding the suitability of products for certain types of applications are based on Advanced Photonix's knowledge of typical requirements that are often placed on Advanced Photonix products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each custo ty+mer application by the customer's technical experts. Product specifications do not expand or otherwise modify Advanced Photonix's terms and conditions of purchase, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, Advanced Photonix products not ex

MATERIALS SAFETY

This product is free of conflict minerals and meets REACH compliance. Please see website for reports.

Rev: A August 17, 2021 © 2021 Advanced Photonix. All rights reserved.