

## Datasheet Plastic Collimator Lens CAY033-40-2

These data concern a full plastic bi-aspherical lens. It is specified for use as a collimator in combination with a diode laser. It can be mounted by use of glue or spring-loaded. Mechanical lock-mounting is not advisable because of possible distortions.

Parameters	Wavelength 670 nm	Unit
<b>Design conditions</b>		
<i>N.A.</i>	0.38	--
Clear Apertures <i>CA</i>	2.5	mm
Designed with laser cover glass ( <i>BK7</i> ) on source side:		
Distance from source	0.55	mm
Glass thickness	0.25	mm
<b>Optical parameters</b>		
Focal Length	3.35	mm
Back Focal Length <i>BFL</i> ( <i>with BK7 coverglass</i> )	2.07	mm
Free Working Distance <i>FWD</i>	1.97	mm
<i>RMS</i> mean	on axis	30
		mλ
<i>RMS</i> max. ( $\pm 3\sigma$ )	on axis	40
		mλ
Optical Tolerance	0.1	mm
Field Radius	0.05	mm
<b>Mechanical parameters</b>		
Mounting hole diameter $D_{mh}$	∅ 4.00 (+ 0.03)	mm
Other parameters:	see drawing	
<b>Environmental stability</b>		
Storage Temperature	-25 to 70	°C
Operating Temperature	5 to 65	°C

### General Data:

Transmission [%]: > 90

Lens Material: Acrylic PMMA [8N]

Specifications subject to change without notice.  
Zemax catalogue file available.

All rights are reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.

Alle rechten voorbehouden. Vervelvoudiging, geheel of gedeeltelijk is niet toegestaan dan met schriftelijke toestemming van de auteursrechtbehebende.

